



Contents

1	Installation	3
1.1	Requirements	3
1.1.1	Operating System	3
1.1.2	System Libraries	3
1.2	Quick Install	3
1.3	Complete control of Building	3
1.4	Complete control of Installation	5
2	Usage	5
2.1	Synopsis	6
2.2	Live Capture vs Trace Analysis	8
2.3	More Control	10
3	Output	10
3.1	Logs	12
3.2	Histograms	12
3.3	RRD	14
3.4	Packet Level Traces	14
3.5	Post Processing	15
3.6	Storage Considerations	15
4	RRD Module	16
4.1	RRDtool Installation	16
4.2	RRD Configuration	16
4.3	Tstat RRD and the Web	17
4.3.1	Database Structure	17
4.3.2	Web Configuration	18
5	Runtime Module	18
6	DPMI Module	21
6.1	Tstat Configuration for DPMI	21
6.2	DPMI Configuration for Tstat	22
7	Bayesian Classification of Skype Traffic	22
8	Libtstat library	25
8.1	Link the Libtstat library	25
8.2	Libtstat API	26

9 Author Informations	27
10 Acknowledgment	27
11 License	27

1 Installation

This document provides basic information for the installation, configuration and usage of Tstat and the Bayesian framework for Skype traffic identification. A more general description of the program as well as other documentation can be found in the Tstat homepage <http://tstat.tlc.polito.it>

1.1 Requirements

1.1.1 Operating System

Tstat has been tested on Linux 2.2.x, 2.4.x and 2.6.x kernels, using RedHat 6.x-9.x, and Fedora Core x systems. It should work under other UNIX dialects, such as FreeBSD, NetBSD 1.3 and MAC OS X (although we do not have any of those platforms for testing purposes). If you are able to run Tstat on other OSs, we will be happy to include them in the list.

1.1.2 System Libraries

Tstat requires, by itself, a few library that should already be installed on your system, such as libpcap (available from <http://www.tcpdump.org>) and the DAG drivers (available from <http://www.endace.com>), in case you use such hardware. With these libraries, you are ready to capture and process the traffic flowing in your LAN.

Since Tstat uses pthread to improve the performance in case of real time analysis, your system must support POSIX threads as well if you want to profit of this feature. However, keep in mind that threaded execution is only an optional feature, and is necessary only for online traffic analysis, so that this is not a strict requirement: for this reason, threading is disabled by default.

Finally, to use the RRD functionalities, you also need to have a working installation of RRDtool (available from <http://oss.oetiker.ch/rrdtool/>).

1.2 Quick Install

Assuming that you want version 2.x.y:

```
wget http://tstat.polito.it/download/tstat-2.x.y.tar.gz
tar -xzf tstat-2.x.y.tar.gz
cd tstat-2.x.y
./autogen.sh
./configure [--enable-libtstat] [--enable-zlib]
make
make install (with root privileges)
```

This commands install a executable file named tstat in /usr/local/bin.

1.3 Complete control of Building

The most important elements in the Tstat's package are:

```
tstat/  
tstat-conf/  
libtstat/  
include/  
libtstat-demo/  
doc/  
doc/HOWTO  
README AUTHORS NEWS INSTALL ChangeLog
```

The `tstat` directory contains the source code of `Tstat` which is also the default building target. Beside `Tstat` it can also be compiled the `Libtstat`, a shared library which allows to an external program to access to the traffic analysis functions of `Tstat`. In the `include` directory there is the header file of the library instead in the `libtstat-demo` directory there is a simple program of example that shows how to use the `Libtstat` (see `Libtstat` library for more information about the `Libtstat` API).

The building of the `Libtstat` library is disabled by default but is provided a configuration option to control this feature

```
./configure --enable-libtstat    # build tstat, libtstat and libtstat-demo  
./configure                      # build only tstat
```

It is possible, if `Zlib` is found on the system, to compile `Tstat` to support the direct creation of `zlib` compressed logs and dump files.

```
./configure --enable-zlib        # build tstat with zlib support
```

At the end of `configure` is printed a small report:

```
-----  
tstat Version 2.4  
-lpcap -lpthread -lm -lrrd -lz  
  
Prefix: '/usr/local'  
  
Package features:  
- pcap      yes  
- zlib      yes  
- rrd       yes  
- libtstat  no  
-----
```

This indicate if the `libtstat` has been selected or not for the building and if either `Librrd` or `Zlib` were found in the system, in which case they are automatically added in building the project.

`Tstat`'s source code uses some preprocess definition to enable/disable some features, like for example the `DAG` support which is disabled by default. These definitions are declared in the `tstat/Makefile.conf` each with a specific description about its purpose so it should be easy change to behaviour in the building process commenting/uncommenting some lines.

NB: remember to run autoreconf from the root of the package every time a change in these file is performed!!!

The building of Libtstat is separated from the building of Tstat so libtstat/Makefile.conf file defines the set of option specific for the Libtstat, while tstat/Makefile.conf is specific for Tstat.

In the directory tstat-conf there are some examples of configuration files needed by Tstat; for example the set of local addresses (-N option), the configuration of the histograms (-H), RRD tool (-R), runtime (-T) and bayesian framework (-B).

In the directory doc there are some plain text files that describes the format of logs files generated by the analysis and in doc/HOWTO there is howto document in different file formats. README, AUTHORS, INSTALL, NEWS and ChangeLog instead are plain files that describes some general information about the package like the authors, the last new features of the tools, etc...

1.4 Complete control of Installation

The default prefix for installation is /usr/local so Tstat executable is installed in /usr/local/bin and Libtstat is installed in /usr/local/lib. Anyway a different prefix can be specified at configuration time

```
./configure --prefix=/absolute/path/where/install/tstat
```

Libtstat-demo is only a demonstration tool so is build only a local executable that is not installed.

Libtstat is provided with pkg-config support so a libtstat.pc is installed in /usr/lib/pkg-config and typing

```
pkg-config --cflags --libs libtstat
```

it should appears an output like

```
-I/usr/local/include -L/usr/local/lib -lm -lpthread -lpcap -lrrd
```

that indicates the CFLAGS and LIBS options used in the building process.

2 Usage

There are few things to know to run Tstat: first, you are required to have a knowledge of the network that you want to monitor. Second, there are the few options that are described in this section.

2.1 Synopsis

Tstat primary usage is as a command-line tool; the synopsis of the command is the following:

Usage:

```
tstat [-htuvwpgSL] [-d[-d]]
      [-s dir]
      [-N file]
      [-C file]
      [-B bayes.conf]
      [-T runtime.conf]
      [-z file]
      [-A mask]
      [-H ?|file ]
      [-Z] [-P]
      [-r RRD_out_dir] [-R rrd_conf]
      [-l] [-i interface] [-E snaplen]
      [-f filterfile]
      <file1 file2>
```

Options:

```
-h: print this help and exit
-t: print ticks showing the trace analysis progress
-u: do not trace UDP packets
-v: print version and exit
-w: print [lots] of warning
-c: concatenate the finput files
    (input files should already be in the correct order)
-p: enable multi-threaded engine (useful for live capture)
-d: increase debug level (repeat to increase debug level)

-s dir: puts the trace analysis results into directory
        tree dir (otherwise will be <file>.out)
-N file: specify the file name which contains the
        description of the internal networks.
        This file must contain the subnets that will be
        considered as 'internal' during the analysis.
        Each subnet can be specified in one of the following types:
        - <Network IP/NetMask> on a single line
          130.192.0.0/255.255.0.0
        - <Network IP/MaskLen> on a single line
          130.192.0.0/16
        - Pairs of lines with <Network IP> and <NetMask>
          130.192.0.0
          255.255.0.0
        If the option is not specified all networks are
        considered internal

-M file: specify the file name which contains the
        description of the MAC addresses that are to be considered internal.
        MAC addresses must be in the 6 digit - hex notation.
Example:
```

11:22:33:44:55:66
66:55:44:33:22:11

If this option is specified, the -N param is ignored.

- C file: specify the file name which contains the description of the cloud networks.
This file must contain the subnets that will be considered as belonging to a specific group of networks (cloud) during the analysis.
Subnets are specified like in the -N option.

- H ?: print internal histograms names and definitions
- H file: Read histogram configuration from file
file describes which histograms tstat should collect
'include histo_name' includes a single histogram
'include_matching string' includes all histograms whose name includes the string
special names are:
'ALL' to include all histograms
'ADX' to include address hits histogram
for example, to include all TCP related and the address hits histograms, file should be:
include ADX
include_matching tcp
'adx_mask N' is a special command to define the size of the netmask used to aggregate the address histograms (e.g. 'adx_mask 24' to use the 255.255.255.0 mask)

- g: Enable global histo engine
- S: No histo engine: do not create histograms files
- L: No log engine: do not create log_* files
- 1: Use old (v1) log_mm format
- B Bayes_Dir: enable Bayesian traffic classification
configuration files from Bayes_Dir
- T runtime.conf: configuration file to enable/disable dumping of traces and logs at runtime
- z file: redirect all the stdout/stderr messages to the file specified
- A mask: enable XOR-based anonymization for internal IPv4 addresses.
'mask' is a decimal, octal, or hexadecimal value.
- Z: Create gzip compressed (.gz) log files.
- P: Create gzip compressed (.gz) pcap dump files.
- R conf: specify the configuration file for integration with RRDtool. See README.RRDtool for further information
- r path: path to use to create/update the RRDtool database
- l: enable live capture using libpcap
- i interface: specifies the interface to be used to capture traffic
- E snaplen: specifies the snaplen size used to capture traffic.
It might be overridden by the interface slen size
- f filterfile: specifies the libpcap filter file. Syntax as in tcpdump

- file: trace file to be analyzed
Use 'stdin' to read from standard input.

Note:

When tstat is called with no arguments (on the command line), it will first check if a file <tstat.conf> is provided in the same directory where the execution started. In the latter case, arguments will be read from <tstat.conf> rather than from the command line

Supported Input File Formats:

tcpdump	tcpdump format -- Public domain program from LBL
snoop	Sun Snoop format -- Distributed with Solaris
etherpeek	etherpeek format -- Mac sniffer program
netmetrix	Net Metrix format -- Commercial program from HP
ns	ns format - Network simulator ns2 from LBL
netscout	NetScout Manager format
erf	Endace Extensible Record format
tcpdump live	Live capture using pcap/tcpdump library

2.2 Live Capture vs Trace Analysis

Tstat can sniff and analyze traffic on-line through the use of either the libpcap library or Endace DAG cards. The use of Tstat is very easy, especially if you have experiences with tcpdump, although tcpdump's knowledge is not required to profitably use Tstat. Moreover, advanced users will enjoy the ability of on-line processing of traffic captured with DAG cards.

As a minimal configuration, you must describe your network to Tstat. Indeed, in order to distinguish forward and backward paths, Tstat needs to know which host IP addresses can be considered as "internal" to the monitored network. There are three different format to specify the internal subnets and if, for example, we use Politecnico di Torino subnets, which are 130.192.0.0/16 and 192.204.134.0/24, we can choose to use one of the following formats:

<Network IP/MaskLen> on a single line

```
130.192.0.0/16
192.204.134.0/16
```

<Network IP/NetMask> on a single line

```
130.192.0.0/255.255.0.0
192.204.134.0/255.255.0.0
```

(only for backward compatibility) pairs of lines with <Network IP> and <NetMask>

```
130.192.0.0
255.255.0.0
192.204.134.0
255.255.0.0
```


Note that formats can be mixed in the configuration file and comment lines can be specified using '#' so using following configuration is still correct

```
# this is a comment
130.192.0.0/24
192.204.134.0/255.255.0.0
192.168.0.0
255.255.0.0
```

In the directory `tstat-conf` are placed the two files `net.all` and `net.private`

```
>cat tstat-conf/net.all
# Mask to indicate that all IP subnets are supposed to be internal
# The same result is obtained omitting the -N option
0.0.0.0/0.0.0.0

>cat tstat-conf/net.private
# Example mask to consider as internal all the subnets in the
# 198.168. private addresses range
192.168.0.0/16
```

that can be useful for generic elaborations. In any case, if the `-N` option is not specified all networks are considered internal.

We can now run Tstat to capture the traffic flowing across our network, with the following command, which must be run as root (as you need to capture packets by putting the Ethernet interface in promiscuous mode). The simplest command is the following:

```
./tstat -l -N net.conf
```

Beside live-capture, it is possible to run Tstat on a previously collected trace file, where the trace format can be any of the following:

Supported Input File Formats:

<code>tcpdump</code>	<code>tcpdump</code> -- Public domain program from LBL
<code>snoop</code>	Sun Snoop -- Distributed with Solaris
<code>etherpeek</code>	<code>etherpeek</code> -- Mac sniffer program
<code>netmetrix</code>	Net Metrix -- Commercial program from HP
<code>ns</code>	<code>ns</code> -- network simulator from LBL
<code>netscout</code>	NetScout Manager format
<code>erf</code>	Endace Extensible Record Format
<code>DPMI</code>	Distributed Passive Measurement Interface (DPMI) format
<code>tcpdump live</code>	Live capture using pcap/tcpdump library

Tstat will try to read trace files given as input, and to automatically identify the correct dump format. Trace files can be compressed or uncompressed, and Tstat will automatically detect the compression tool used (supported formats are `compress`, `gzip`, `bzip2`, `7z`).

Without loss of generality, we assume to use the first of the above formats. The calling syntax is similar to the previous one, with the exception of the absence of the live-capture switch `-l` and the presence of the name(s) of the file(s) that have to be processed. For example, the following command can be used to analyze a trace file named `LAN.dump.gz`. Results of the analysis will be stored in a subdirectory named `trace1`; as before, `net.conf` contains the subnet description that will be considered as "internal" during the analysis.

```
./tstat -s trace1 -N net.conf LAN.dump.gz
```

2.3 More Control

We can control the interface that we want to sniff from as well as the output directory name as follows:

```
./tstat -i eth1 -l -s test -Nnet.conf
```

Moreover, we can also pipe Tstat input using the special keyword `stdin` as input, as in the following command (piping `ns2` output to Tstat is left as an exercise for the reader):

```
tcpdump -s 80 -i eth0 -w - ip | ./tstat -Nnet.conf -spiped stdin
```

In this case, Tstat is fed by `tcpdump`'s output, and the latter has been instructed to capture packets on the `eth0` device, collecting the first 80 bytes (to track uniquely packet headers) of IP packets only, and send the output to `stdout`. Moreover, since Tstat understands the `libpcap` syntax, filters can be stored in text files, as in the following command sequence:

```
echo "vlan and ip and host 10.0.0.1" > tcpdump.conf
./tstat -i eth0 -l -f tcpdump.conf -N net.conf -s filtered
```

3 Output

Tstat collects several network-layer as well as transport-layer measurements, which are described in full details in <http://tstat.polito.it/measure.shtml>. As output, Tstat produces four different types of files: histograms, round robin database, packet level traces and other plain text logs.

By default Tstat collect all the output results in a directory with the same name of the input trace appending the suffix `.out` or `stding` in case of a live capture:

```
./tstat -N net.conf trace1.pcap trace2.pcap # output dir: trace1.pcap.out, trace2.pcap.out
./tstat -N net.conf -li eth0                # output dir: generate stdin
./tstat -N net.conf -s trace1 trace1.pcap    # output dir: trace1
```


In any case, inside the output directory is generated a subdirectory named with the timestamp of the first packet analyzed and inside this directory the files generated are organized as follow:

```
<output_root>
'-- 23_00_28_Jun_2008.out
  |-- 000
  |   '--- histo_logs
  |-- 001
  |   '--- histo_logs
  ...
  |-- LAST
  |   '--- histo_logs
  |
  |-- traces00
  |   '--- dump_traces
  |-- traces01
```

```
|   '-- dump_traces
...
'-- other_logs
```

This means that the RRD output files are not collected inside the output directory, in fact there is a specific command line option (-r) to indicate where this results have to be placed.

Recall that Tstat assumes that traces are collected on a bidirectional link, such that both data and control packets belonging to the same flow are observed; with the help of the figures below, we will explain the different classification of measurements used by Tstat.



Tstat identifies hosts based on their IP address. Given the description of the internal hosts through the -N command line option, Tstat distinguishes among *incoming*, *outgoing* and *local* measurements. Packets whose destination is an internal host and whose source is an external host will contribute to *incoming* measurements (red arrow in the top figure), whereas packets going in the opposite direction will contribute to *outgoing* measurements (green arrow in the top figure). Finally, in some cases it is possible that Tstat observes packets whose source and destination host belong to the internal host set: in such cases, measurements will be classified as *local* (blue arrow in the top figure). Notice that packets whose source and destination IP addresses belong to the external host set will be discarded. For example, consider a setup in which Tstat is attached to a snoop port of a LAN switch. Then Tstat will be fed by i) *outgoing* packets going to the default gateway, ii) *incoming* packets coming from the default gateway, iii) *local* packets.

Note that if you either do not know or do not want to distinguish between internal, external and local hosts, you may enable the -DLOG_UNKNOWN (in tstat/Makefile.conf or libtstat/Makefile.conf) directive when compiling. Tstat will then be less strict, but results may be difficult to be correctly interpreted.

Considering instead the *role* of the host that sent the packet, statistic are collected distinguishing between *clients* (green arrow in the bottom figure) and *servers* (red arrow in the top figure), i.e., host that opens a connection and host that replies to connection request. Recall that while TCP connections are well defined, UDP (and RTP/RTCP) connection definition is more fuzzy. In this latter case, Tstat will consider as client the source IP address of the host that sent the first packet of that flow, while the server will be the host identified by the destination IP address of the same packet.

Therefore, when applicable, Tstat will keep track of measurements referring to the same measured quantity by *appending* a specific tag (see Sec. 3.2) or using a *flag* (see *Logs*).

3.1 Logs

Tstat creates a set of TXT flow files in the main output directory: `log_tcp_complete`, `log_tcp_nocomplete`, `log_udp_complete`, `log_mm_complete`, `log_video_complete`, `log_skype_complete`, `log_chat_complete` and `log_chat_messages`. TCP flows can be either completed or not depending whether Tstat observed the 3-way handshaking or not; in the first case, all the measured indexes relatively to each flow will be collected in the `log_tcp_complete`; in the latter case, flows are considered as garbage and stored in `log_tcp_nocomplete`; Similarly, a complete log keeping track of each UDP flow measured indexes is maintained in the `log_udp_complete` file. Being UDP basically a connectionless protocol, it is impossible to distinguish among complete and nocomplete flows in this case.

Furthermore the following log files are created: `log_video_complete` and `log_streaming_complete` for TCP video streaming flows (i.e. RTMP or HTTP-based video services like YouTube), `log_mm_complete` for multimedia flows (i.e. RTP, RTCP, etc), `log_chat_complete` for IM protocols (i.e. MSN, Jabber, etc) and `log_skype_complete` for Skype traffic.

Description of the file format of each log file can be found in <http://tstat.polito.it/measure.shtml>.

If Tstat has been compiled with Zlib support, it will directly create gzip compressed logs (.gz) when the command line option `-Z` is used. Internal compression might be CPU demanding: before enabling it, you should consider its possible effects on the Tstat performance.

3.2 Histograms

Histograms are generated periodically to generate the *distribution* of a given quantity within a time interval. Tstat collects all the measurement data during a given measurement interval defined by the `MAX.TIME.STEP` parameter, which is hard-coded in the `tstat/param.h` file to 5 minutes. Please, note that changing the `MAX.TIME.STEP` parameter may affect RRD creation as well. For example, considering the IP packet length, Tstat updates, for each observed IP packet, the counter of the number of observed packets with a particular length. At the end of the measurement period, Tstat then saves the values stored in the histogram in a subdirectory named with an incrementally counter of three digits, resets all the internal values, and then restarts the samples collection.

To separate statistics respecting the verse (input, output or local) and the role of a peer in the communications, is appended a tag to files generated:

`_out`

outgoing: from an internal host to an external host

`_in`
incoming: from an external host to an internal host

`_loc`
local between two internal hosts

`_c2s`
going from the Client to the Server

`_s2c`
going from the Server to the Client

Considering the last example of previous section, we run:

```
./tstat -s trace1 -N net.conf 23_00_28_Jun_2008.dump.gz
```

The output generated by Tstat consists of a directory tree like the following:

```
trace1
'-- 23_00_28_Jun_2008.out
|  |-- 000
|  |  |-- addresses<tag>
|  |  |-- flow_number<tag>
|  |  |-- ip_len_in<tag>
|  |  ...
|  |  |-- udp_port_flow_dst<tag>
|  |  '-- udp_tot_time<tag>
|  |-- 001
|  |  |-- addresses<tag>
|  |  |-- flow_number<tag>
|  |  |-- ip_len_in<tag>
|  |  ...
|  |  |-- udp_port_flow_dst<tag>
|  |  '-- udp_tot_time<tag>
|  ...
|  |-- LAST
|  |  |-- addresses<tag>
|  |  |-- flow_number<tag>
|  |  |-- ip_len_in<tag>
|  |  ...
|  |  |-- udp_port_flow_dst<tag>
|  |  '-- udp_tot_time<tag>
```

Subdirectories with increasing numbers will be created for each measurement period with the format `nnn/`; histograms collecting measurement results will be created in these directories; note that the histograms referring to the last *partial* time period will be stored in the LAST subdirectory. The option `-g` adds also the subdirectory GLOBAL containing the global histograms for the whole measurement period.

The `-H` has to be used to enable the histogram engine, specifying a configuration file of ? to have a complete list of the available histograms. The syntax of the configuration file is really simple:

```

include ALL          # add all histograms
include ADX          # histogram to count how many times ip address are used
adx_mask 16          # define the size of the netmask for the ADX histogram

include ip_len_in     # histogram of the ip packet length of the input traffic

include_matching ip_   # match all the histograms which name start with 'ip_'

```

Histogram data are saved using simple ASCII files: the first line contains a description of the measured quantity, while the second line contains the parameters of the histograms (minimum and maximum values, and size of each bins). The list of all the counter index and values is then dumped. To limit the file size, the corresponding entry is omitted if the counter is zero. For example, the histogram of the packet length `ip_len_in` looks like:

```

#IP packet length - incoming packets
#min=0 bin_size=4 max=1600
28 7
36 277
40 11760
44 3463
...

```

Simple Post Processing tools are available to automatically manage the histogram database.

3.3 RRD

The RRD output consists of a series of binary files stored in the RRD format. Tstat forces a particular *naming notation* of such files, which follows the configuration rules described later in Sec. 4.2.

The RRD can then be queried with the standard RRDtool commands, such as `rrdcreate`, `rrdupdate`, `rrdgraph`, `rrddump`, `rrdfetch`, `rrdtune`, `rrdlast`, `rrdexport`, to whose manual pages we refer the reader for further informations.

3.4 Packet Level Traces

Inside Tstat there is a Deep Packet Inspector - DPI which is able to identify traffic communications at application level looking the composition of the payload of packets.

This feature is controlled by the Runtime module and the output files are placed in sub-directories named `tracesNN` where `NN` is an counter incremented every time the runtime configuration is changed. In any case, for each configuration, the input traffic in is splitted in traces with windows of 1 hour, that is, for example, if we start the dump at 9:00 am

```

traces00/udp_complete.pcap0    #all the udp traffic from 9:00 to 10:00
traces00/udp_complete.pcap1    #all the udp traffic from 10:00 to 11:00
...

```

All the traces are in pcap format and, because of the level 2 headers are in general useless for statistic purpose, each packet dumped is composed of a bogus Ethernet header (contains only zeros expect for the type field which is IP) followed by the original packet starting from

IP header. The input packets can also be truncated after a specific amount of bytes which can be configured using the `snap_len` specific option in the configuration file.

If Tstat has been compiled with Zlib support, it will directly create gzip compressed traces (.pcap.gz) when the command line option `-P` is used. Internal compression of the packet traces is highly CPU demanding: before enabling it, you should consider its possible effects on the Tstat performance.

3.5 Post Processing

This section could be a separate HOWTO, since this argument cannot be treated exhaustively. Perl, Awk, Ruby *Your-Favorite-Scripting-Language* scripts are definitively best candidates to post-process `log_*` files.

In the Tstat download page and in the source archive, you can find `plot_time.pl` and `plot_cum.pl`, two Perl scripts that may be useful to produce either i) time or ii) aggregated plots over different time spans. They directly access the histogram database created by Tstat. Please, refer to <http://tstat.polito.it/software.php#postprocess>.

In the source code, in `scripts/MySQL/`, you can also find a few Perl scripts to load the main `log_*` files in a simple MySQL database, for further post-processing.

RRD files can be manipulated to obtain *indirect* metrics through the RPN manipulations mechanism provided by RRDtool.

3.6 Storage Considerations

To give the user a rough idea of the size of the output, let us consider a 6 hours long, 1.6GB packet-level trace containing 21M packets, sniffed with `tcpdump` that was used throughout this tutorial. Tstat identified and analyzed about 729K flows, of which about 495K were TCP flows, trashing 20K of them into `log_nocomplete`. Referring to the Sec. 3 above shown, we can express the following observations:

Histogram

As previously described, in order to take into account the flow directions, several histograms are dumped for the same variable `var_{in,out,loc,c2s,s2c}`. Currently, about 60 measurement indexes, described in <http://tstat.tlc.polito.it/measure.shtml>, are logged, for a total of 180 files. Each of the `000/`, `001/` ... `LAST/` directories is about 500KB-1MB depending on the network traffic and on the file system block allocation mechanism.

Therefore, as a rule of thumb, you can count about 1MB of storage due to histograms every 5 minutes of traffic (independently of the amount of actual traffic load during the 5 mins...). This can be useful in order to set the periodic dump timer to the desired trade off among time granularity versus storage size required.

RRD

The `rrd/` directory is, per construction, of fixed size: this should not be a surprise, since this is the goal of RRD. Therefore, the size of the database does not depend on the amount of network traffic processed, but rather on the RRD configuration. For the standard configuration supplied with Tstat, which is also the one used in our Web server, the whole database occupy only 6MB and consists of about 250 files.

Logs

The total size of the log files amount to about 200MB, which gives a 8x reduction factor w.r.t. the packet-level trace; or, the storage cost of each flow is about 400 bytes.

Note that the `log.*` can be further compressed, using the `-Z Tstat` command line option or `gzip` to less than 50MB, which gives a further 4x size gain; however, for a matter of performance, is preferable to compress the log files *offline*.

Finally, consider that on a common PC architecture (specifically, Intel P4 2.40GHz equipped with 2GB of RAM and 7200rpm hard-disk), the whole trace elaboration took only 4 minutes; thus, the analysis rate is roughly 85Kpkts/sec or 3Kflows/sec.

4 RRD Module

4.1 RRDtool Installation

In order to get Tstat RRD module working, you will need to install RRDtool first (refer to the homepage of RRDtool <http://oss.oetiker.ch/rrdtool/> to accomplish this step). The autoconf file `configure` of Tstat then should automatically add the RRD support if it find one (see Sec. 1.3).

4.2 RRD Configuration

Tstat RRD configuration is very easy, being centralized in a single text-file, which allows to specify at runtime what measurements should be monitored. The operating frequencies for the RRD sampling (i.e., the parameters for the temporal averages) are hard-coded into `rrdtool.h` and are chosen to mimic MRTG behavior. Again, take care that modifying the `MAX_TIME_STEP` parameter may affect the RRD management as well.

The RRD configuration file, specified through the command line option `-R`, should contain one line for each of the Tstat parameters that have to be integrated into a Round Robin Database. Each line allows to specify which statistical properties of the variable has to be tracked, as follows:

```
tstat_var1 avg min max stdev var idx:e,f,g,h,other prc:i,j,k
```

where `avg,min,max,stdev,var,idx,prc,other` are keywords, whereas `i,j,k` are floating point numbers and `e,f,g,h` integer values; note that the list of indexes (e.g., TCP ports), values (e.g., packet size) and percentiles are comma separated. The name of the variables are Tstat internal ones: they can be seen by executing `./tstat -H`. Alternatively, you can directly look into the `000/ ... LAST/` directories or or at <http://tstat.polito.it/measure.shtml>

Valid configuration lines are, e.g.:

```
#
# inspect IP packet length average, specific values and distribution
#
ip_len_in    avg prc:50,90,95,99 idx:40,1500,other
```



```

#
# TCP well known ports
#
# 20    FTP-DATA
# 21    FTP
# 22    SSH
# 23    telnet
# 25    SMTP
# 80    HTTP
# ...
#
tcp_port_dst_in      idx:20,21,22,23,25,80,other

#
# good approximation of the distribution of the RTT,
# taking into account only the incoming path contribution
#
tcp_rtt_avg_in      prc:0.1,1,5,10,25,50,75,90,95,99,99.9

```

where, evidently, the lines starting with a # sign are treated as comments. Our Web server is currently running with the configuration available at <http://tstat.polito.it/download/rrd.conf>.

For each specified quantity defined in the rrd.conf file, a corresponding file will be created. For example, consider that the generic configuration line:

```
tstat_var avg min max stdev var idx:e,f,g,h,other prc:i,j,k
```

will produce the following files (13 in total):

```

tstat_var.{avg,min,max,stdev,var}.rrd
tstat_var.idx{e,f,g,h,oth}.rrd
tstat_var.prc{i,j,k}.rrd

```

4.3 Tstat RRD and the Web

From the Tstat web site, you can download the most up-to-date version of `tstat_rrd.cgi`, which is the CGI script that renders the Web interface. Here is some basic tips to get it working; if you wonder how to write your own graph templates, then you are probably skilled enough to get it on your own :)

4.3.1 Database Structure

The CGI scripts allow to browse on the fly the RRD database structure. The `rrd_data` directory is the root of the tree, where each directory contains either i) other directories (i.e., is a box) or ii) a RRD-database, in which case the node is a leaf and will be shown in the interface. In case that a directory is a plain box, it may optionally contain some files (specifically `{HEADER,FOOTER,README}.{html,txt}`) that will be rendered by `tstat_rrd.cgi`. By default, the cgi script tries to load the html version; otherwise, it tries to displays "`<pre> 'cat FILE' </pre>`" if such a FILE exists; finally, it will display a default message held in `$default{README}` hard coded in the script.

Here is an example of the `rrd_data` directory which holds part of the RRD database accessible from the Tstat web page.

```

rrd_data/
|-- Example
|-- GARR
|   |-- garr-live
|   '-- garr-old
'-- Polito
    |-- 2000
    |   |-- Apr
    |   |-- Jun
    |   |-- Jun,post155
    |   '-- May
    |-- 2001
    |   |-- Feb
    |   '-- Jan
    |-- 2005
    |   |-- Apr
    |   '-- Feb
    '-- Current

```

4.3.2 Web Configuration

The web configuration really depends on your web server configuration. Few dependencies are required, most notably, the RRD Perl library from the RRDtool installation.

It is advisable to store the Tstat RRD files everywhere you want, and then create a symbolic link named `rrd_data` that points to it (i.e., to the root of the RRD database tree). Similarly for the directory where the rendered images should be stored (defaults to `cgi-bin/rrd_images`) and can be a symbolic link as well. The names of these symbolic links can be redefined in the configuration section of `tstat_rrd.cgi` if needed:

```

# -----
# /                               \
# /      configuration      -----/
# \-----/.:nonsns:.\
#
# specify path to the root of the rrd database tree
# by default, I assume there is a symbolic link in cgi-bin/
# named rrd_data
$RRD_DATA = 'rrd_data';

# same thing for image directory
# in my case, var/www/cgi-bin/rrd_images is
# a symbolic link to "/var/www/html/rrd_images";
# from the html browser's perspective
$IMG_DIR = "rrd_images";

```

5 Runtime Module

This module has been developed with the specific target to try to control the disk occupation and to have a minimal interface to execution process to enable/disable some feature without

restarting it. In particular, the system controls two specific outputs: the writing of log files and packet level traces, so is possible to disable the writing of logs (histograms, RRD and all the others) if they became too big, and to dynamically change the set of packet level traces to collect.

The module works with a simple polling system that is it periodically tests if a configuration file, specified with the -T option when Tstat is executed, is changed from the previous check and in this case, the new configuration replaces the previous one.

The configuration file has an ini file syntax:

```
> cat tstat-conf/runtime.conf
# print logs on disk
[log]
histo_engine = 0      # logs created by histogram engine
rrd_engine = 0        # logs created by rrd engine
log_tcp_complete = 0  # tcp connections correctly terminated
log_tcp_nocomplete = 0 # tcp connections not properly terminated
log_udp_complete = 0  # udp flows
log_mm_complete = 0   # multimedia
log_skype_complete = 0 # skype traffic
log_chat_complete = 0 # MSN/Yahoo/Jabber chat flows
log_chat_messages = 0 # MSN/Yahoo/Jabber chat messages
log_video_complete = 0 # youtube video
log_streaming_complete = 0 # generic video
log_http_complete = 0  # all the HTTP requests/responses

# protocols to dump
[dump]
snap_len = 0          # max num of bytes to dump from ip hdr (included)
                        # 0 == all bytes

udp_dns = 0
udp_rtp = 0
udp_rtcp = 0
udp_edk = 0
udp_kad = 0
udp_kadu = 0          # KadU network
udp_okad = 0          # obfuscated kad
udp_gnutella = 0
udp_bittorrent = 0
udp_dc = 0
udp_kazaa = 0
udp_pplive = 0
udp_sopcast = 0
udp_tvants = 0
udp_ppstream = 0
udp_teredo = 0
udp_vod = 0
udp_sip = 0
udp_unknown = 0      # all the udp traffic that the DPI doesn't recognize

tcp_videostreaming = 0
```

```

ip_complete = 0    # all the ip traffic (not consider L4 type and if it's used)
udp_complete = 0    # all the udp traffic
tcp_complete = 0    # all the tcp traffic

```

```

udp_maxpackets = 0
udp_maxbytes = 0
tcp_maxpackets = 0
tcp_maxbytes = 0

```

```

stop_dumping_mask = 0 # bitmask to control the dumping of tcp packets based on flow type

```

The file is composed of the two sections `log` and `dump` which indicate which type of log and dump trace to create. Except for a few exceptions, all features are on/off type i.e. 1 and 0 values are used to enable/disable them. One exception is `snap_len`, used to indicate the maximum number of bytes dump from the input packet starting from IP level included. For example, supposing to have a simple IP + UDP packet, using `snap_len = 40` it will be written a packet of 54 bytes

```

14 (bogus ethernet) + 20 (IP) + 8 (UDP) + 12 (payload)

```

For UDP traffic it can be specified a set of applications so to have a specific dump trace for each application of interest. The unknown traffic i.e. the traffic that the Tstat's DPI is not able to identify, is placed in a separated trace. For example, using the following configuration

```

udp_rtp = 1
udp_edk = 1
udp_bittorrent = 1
udp_unknown = 1

```

it's expected to have 4 traces i.e. three protocols/applications (RTP, eMule, Bittorrent) and the unknown (for example DNS traffic).

Classified TCP complete flows cannot be "safely" dumped, since classification happens after the 3-way handshaking finished, so saved flows would be incomplete. `tcp_videostreaming` is an exception, used to dump TCP flows that were classified as video through the Streaming DPI engine (the ones logged in `log_streaming_complete`), even if the 3-way handshaking and the first flow payload packets would be skipped. This could be activated if you're interested in performing a secondary analysis on characteristics of the video stream.

Beside the traces at application level, it's possible to create three type of aggregated traces. In particular, `udp_complete` is all the UDP traffic (both applications specific and unknown), `tcp_complete` is all the TCP traffic, while `ip_complete` refers to all the traffic that use IP as level 3 without considering the level 4. In other words, `ip_complete` is the aggregation of TCP, UDP and all the other network protocols that use directly IP (ICMP, IPIP, ESP, ...). The three options are NOT complementary so it's possible to enable all of them contemporary but this obviously means that a TCP/UDP packet it will appear in more than one trace so particular attention should be taken.

When dumping all TCP (`tcp_complete`) or UDP (`udp_complete`) traffic, it is possible to limit the dumping of each flow to either a maximum number of packets or a maximum number of bytes transferred. For example, to save just the first 30000 bytes or the first 30 segments of each TCP flow (whichever condition is reached first), you can use

```

snap_len = 0
tcp_complete = 1
tcp_maxpackets = 30
tcp_maxbytes = 30000

```

udp_maxpackets and udp_maxbytes provide the same functionality for UDP flows. If both xxx_maxpackets and xxx_maxbytes are set to 0, the complete TCP/UDP flows will be saved, with no size limitation.

stop_dumping_mask is a bitmask that is used to stop dumping tcp packets of flows we are not interested to. It is a bitmask based on protocol.h types that the con_type can take. Setting this to 0 will keep logging everything. Setting a bit to 1 will stop logging packets of those protocol as soon as the classifier set those flags (e.g., setting it to 1025 (1+1024), all http and smtp traffic will be discarded). As for other parameters, the value can be set either as a decimal number, or as an hexadecimal number (prefixing it with 0x). Note that we cannot discard those packets of a flow that we have seen before actually identifying the protocol. For example, three-way-handshake segments will be always there. Examples:

```

stop_dumping_mask = 262143 # => 11 1111 1111 1111 1111 discard everything except UNKNOWN
stop_dumping_mask = 262142 # => 11 1111 1111 1111 1110 log only UNKNOWN and HTTP
stop_dumping_mask = 0x3DFFF # => 11 1101 1111 1111 1111 log only UNKNOWN and SSL/TLS
stop_dumping_mask = 1      # => 00 0000 0000 0000 0001 log everything which is not HTTP
stop_dumping_mask = 0      # => log everything

```

During the runtime execution of Tstat, the configuration file is controlled periodically looking for changes in the options. In this way, when Tstat is used for online monitoring, is possible to interact with the dumping module without the need to restart the program. When a change is identified a new tracesNN output directory is created in the root output directory to collect all the new traces and is also generated a file called log.txt that indicate the dump configuration used for that particular dump.

6 DPMI Module

To the experienced DPMI user, it can turn very useful to think of Tstat in terms of a DPMI consumer, thus suitable for live usage. Basically, two configuration files need to be provided in this case.

6.1 Tstat Configuration for DPMI

Especially for this purpose, Tstat can be executed without any argument on the command line, provided that a file named tstat.conf exists in the same path where the tstat command has been executed. Note that the filename MUST be in this case tstat.conf

In the latter case, arguments will be read from tstat.conf rather than from the command line, which makes Web-based execution easier – it just requires the creation of a text file.

Typically, the content of the file will be one of the two following cases. When only the RRD module need to be turned on, which is specially suitable for the persistent monitoring of a network link:

```
-D dpmi.conf -S -R rrd.conf -r data.rrd
```

Or, in the case where more detailed transport layer logs and histograms are to be generated, such as for shorter ad-hoc experiment:

```
-D dpmi.conf -s data
```

Note that the `dpmi.conf` filename, which is the object of the next section, is customizable.

6.2 DPMI Configuration for Tstat

This file is used by Tstat in order to properly set-up the DPMI library and, possibly, its filters. There are only two keywords that are interpreted by Tstat, and *the whole* content of this file is passed to the DPMI's `createfiler` library call. Tstat-keywords are prepended by the `tstat:` prefix, to solve any ambiguity, and are related to the type of stream and measurement direction. More specifically,

```
tstat:(file|(tcp|udp|eth)[:port])
```

Specify whether a tracefile or a network socket (and in this case, which port) is the source of DPMI traffic. Note that in the case where a tracefile is used, there is no real need to specify this, since the format recognition happens automatically; thus, the `tstat:file` keyword is provided for completeness. Conversely, options such as `tstat:eth` and `tstat:tcp:32449` are necessary in order for network sockets to properly be setup.

```
tstat:MP:CI
```

This option is used to define the traffic directionality, specifying what network card interface (CI) and the measurement point (MP) are related to *incoming* traffic from external sources. Referring to the DPMI library internals:

```
CI <-> char nic[8];  
MP <-> char mampid[8];
```

In order to provide a safe fallback or a missing configuration, unless otherwise specified, the first received frame is assumed to be “incoming”, thus arbitrarily determining the incoming CI:MP couple.

7 Bayesian Classification of Skype Traffic

The Bayesian framework is configured through a directory (`-B` command line option) containing several configuration files. A example of configuration is provided under the `tstat-conf` directory so please refer to this directory reading this explanation. In the configuration directory two files have to be placed, named `pktsize.conf` and `avgipg.conf` which define the parameters used by the classification framework to describe the **packet size** and **average inter-packet gap**.

Both files have the same format specified in the example below:

```

# -----
# /           \
# /   BayesConf   \
# \-----/
# \-----/..:nonsns:.
#
#=====
# feature name
#-----
# Known Skype features:
#     PKTSIZE
#     AVGIPG
#
FEATURE    AVGIPG
#
#=====
# default flags
#-----
# USE_LOG      1
# NORMALIZE    1
# AUTO_OTHER   0
#
WINDOW_SIZE   1
CLASS_LEN     250
MIN_THRESHOLD 1e-25
AVG_THRESHOLD -3.5
WIN_THRESHOLD -3
#
#=====
# class definition
#-----
# syntax
#     DISCRETE   class P{class}
#     GAUSSIAN   class P{class} mu sigma
#     GAUSSIAN+  class P{class} N (w1,m1,s1) .. (wN,mN,sN)
#
# note: P{class} may be "="
#
GAUSSIAN mode1 = 10 2
GAUSSIAN mode2 = 20 2
GAUSSIAN mode3 = 30 2
GAUSSIAN mode4 = 40 2
GAUSSIAN mode5 = 50 2
GAUSSIAN mode6 = 60 2

```

The keyword FEATURE is used to specify which type of statistic the configuration file is referred to. In the example above we are dealing with the average inter-packet gap, and specifying PKTSIZE we will describe packet size feature.

Each feature then has a set of flags and other options values that can be used to change the configuration of the NBC engine. Default parameter are strongly suggested, but in case you want to experiment with different combinations, you can try to change them.

USE_LOG:

If set to 1, the function $\log_{10}()$ is applied to the probability values instead to use the actual probability value; this avoids eventual underflow errors when dealing with very low probabilities.

NORMALIZE:

If set to 1, the beliefs computed are re-normalized in the range 0:1; this option is valid only if USE_LOG is disabled (by default is enabled);

WINDOW_SIZE:

The number of packets after which recompute beliefs (by default after each packet);

CLASS_LEN:

The maximum value assumed by the feature and is used to compute class probability distribution functions (by default is 0);

MIN_THRESHOLD:

A positive small value that replace the value 0 in the computation of beliefs to avoid underflows because of logarithm function (by default $1e-33$);

AVG_THRESHOLD:

The static threshold used to compare the maximum computed belief and take the classification.

WIN_THRESHOLD:

A static threshold is used to count the number of individual samples (rather than their mean) that passes a more restrictive test (indeed the window threshold is greater than the average threshold).

Important configuration parameters are the “modes” which must be carefully defined. Modes are the set of p.d.f. that describe the expected distribution of the feature.

Modes may be described as a DISCRETE function, that is a generic distributions, or as a GAUSSIAN function, that is a gaussian (or a superposition of a gaussian) distribution.

Each mode then is associated with a name and a probability which is used as a weight. If '=' is used instead of a weight specific values, all weight are assumed to be uniform.

The special type GAUSSIAN+ may be used to define a mode composed of N different gaussian distributions. Each function is defined by mean and standard deviation sigma and the weight of the mixture have to be specified.

Assuming that you have configured both average ipg and packet size feature in a directory named bayes_conf_dir the classification engine can be enabled simply specifying the -B command line option:

```
# using live capture mode
./tstat -l -B <bayes_conf_dir> -N net.conf

# using a packet dump trace
./tstat -B <bayes_conf_dir> -N net.conf tracefile.dump
```


8 Libtstat library

Libtstat is a shared library that can be used by external programs to access to the statistics and classification features provided by Tstat. As described in the Install section of this document, to enable the building of Libtstat library is needed to provide a configure option

```
./configure --enable-libtstat
```

8.1 Link the Libtstat library

When the library is installed in the system using `make install` the following messages are printed on the console

```
-----  
Libraries have been installed in:  
/usr/local/lib
```

```
If you ever happen to want to link against installed libraries  
in a given directory, LIBDIR, you must either use libtool, and  
specify the full pathname of the library, or use the '-LLIBDIR'  
flag during linking and do at least one of the following:  
- add LIBDIR to the 'LD_LIBRARY_PATH' environment variable  
  during execution  
- add LIBDIR to the 'LD_RUN_PATH' environment variable  
  during linking  
- use the '-Wl,--rpath -Wl,LIBDIR' linker flag  
- have your system administrator add LIBDIR to '/etc/ld.so.conf'
```

```
See any operating system documentation about shared libraries for  
more information, such as the ld(1) and ld.so(8) manual pages.  
-----
```

This indicate where the library has been installed and how to link that to some program. The most simple thing to do, is to use the native libtool support for automake, that is, assuming that `program_name` is the name of the executable of the tool to generate, it is needed to add the following lines to `Makefile.am` of the tool:

```
program_name_LDADD = -ltstat -lpcap -lpthread -lm  
program_name_LDFLAGS = -Wl,--rpath -Wl,<libtstat_dir>
```

This allow a fined control on the directory where the library has been installed. Anyway, if it has been installed in a standard library location (as `/usr/lib`), instead of the previous lines, it can be added

```
AC_CHECK_LIB([tstat], [tstat_next_pckt],, AC_MSG_ERROR([missing 'tstat' library]))
```

in `configure.ac` of the current project. This automatically look for the presence of a function `tstat_next_pckt()` in a system library named `libtstat`. In case of error of error print a message stopping the configuration process, instead in case of success, are automatically added all the linking options needed to build the program (see the autotools files in `libtstat-demo` for a complete example).

8.2 Libtstat API

Tstat's elaborations are performed starting from the level 3 (IP) so its input is a simple array of bytes that contains a packet starting from level 3. This means is the external program that has to open a trace or read a packet from a network card and to parse all the level 2 headers just to have a pointer to the IP header. From this point of view, it can be said that Tstat is simply a wrapper around Libtstat that add only the support to parse a set of level 2 headers.

int tstat_init (char *config_fname)

config_fname is a file name containing a set of Tstat options, one for each line

```
>cat tstat-conf/tstat.conf
#-s outdir      # output directory
-N net.all      # network config file
#-B bayesdir    # directory of the bayes config files
#-d             # debug
```

If NULL is provided, the library use ./tstat.conf as filename.

void tstat_new_logdir (char *filename, struct timeval *pckt_time)

This function has to be called before the process of the first packet and allow to generate the output directory using this hierarchy:

```
<filename>.out
|__<pckt_time>.out
```

int tstat_next_pckt (struct timeval *pckt_time, void *ip_hdr, void *last_ip_byte, int tlen, ip_direction)

This function enable the processing of a new packet. pckt_time is the timestamp of the packet, ip_hdr is a pointer to the first ip byte, last_ip_byte is a pointer to the last ip byte, and tlen is the number of total bytes (captured). Instead ip_direction indicates if the packet is incoming or outgoing. Possible values :

- 0: use the address based classification provided by the -N option
- 1: packet is treated as having internal source and internal destination (local packet)
- 2: packet is treated as having internal source and external destination (outgoing packet)
- 3: packet is treated as having external source and internal destination (incoming packet)
- 4: packet is treated as having external source and external destination (external packet, will be ignored)

tstat_report *tstat_close (tstat_report *report)

This function flush to file all the pending statistics and fill a tstat_report structure with some general results.

void tstat_print_report (tstat_report *report, FILE *file)

This function print a formatted report to file using tstat_report data.

9 Author Informations

Active authors:

Maurizio Munafo' <munafo@polito.it>
Alessandro Finamore <finamore@mail.tlc.polito.it>

Other active authors:

Marco Mellia <mellia@mail.tlc.polito.it>
Dario Rossi <dario.rossi@enst.fr>
Vinicius Gehleb <vinicius@gehlen.us>

Other authors:

Andrea Carpani, Luca Muscariello, Dario Bonfiglio, Robert Birke

Other links:

Telecommunication Networks Group (TNG)
DELEN, Politecnico di Torino
<http://www.tlc-networks.polito.it>

10 Acknowledgment

Many people contributed to the development of Tstat. Tstat would never have seen the light had not TCPTrace being invented. Many thanks to Shawn Ostermann and to the Ohio University for their great program.

Many Master and PhD students took part in the development and debugging of Tstat. Naming all of them would be impossible. We would then like to thank Luca Muscariello for the entropy generated in the TCP anomalies identification, and Prof. Marco Ajmone Marsan and Prof. Fabio Neri who gave us the moral and scientific support to continue investing in Tstat.

11 License

Copyright (c) 2001-2014 Politecnico di Torino. All rights reserved.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.